

24024 SERIES BATTERY DISCONNECT SWITCH

175A • 36V • Single Pole, Single Throw





Description

The 24024 battery disconnect switch is a 175A, 36V Single Pole, Single Throw (SPST) manual disconnect switch that can be used to disconnect the battery from the vehicle electrical system. Disconnecting the battery from the electrical system prevents potential thermal events and ensures system shut down during maintenance or emergency. Battery disconnect switches also prevent parasitic loads from draining the battery during inactivity.

Web Resources

Download 2D print and technical resources at:

littelfuse.com/24024

Features and Benefits

- Rugged steel case
- O-ring and gasket sealing throughout
- Silver plated contacts for high conductivity and low contact resistance.
- Removable Hencol key for security
- Anti-rotation locator pin enables ease of mounting

Specifications Overview

Amperage: 175A

Max Input Current: 1000A for 15 seconds

Voltage Rating: 36V DC

Circuitry: Single Pole, Single Throw

Housing: Plated Steel

Contacts: Two Silver Plated Brass Studs (3/8-24)

Applications

- Heavy Duty Truck
- Construction
- Emergency Vehicles
- Bus/Transit
- Agriculture

Ordering Information

PART NUMBER	DESCRIPTION
24024	175A, 36V, SPST Battery Disconnect Switch



Visit Littelfuse.com for the most up-to-date product information. Littelfuse products are designed for specific applications and should not be used for any purpose (including, without limitation, automotive applications) not expressly set forth in applicable Littelfuse product documentation. Warranties granted by Littelfuse shall be deemed void for products used for any purpose not expressly set forth in applicable Littelfuse product documentation. Littelfuse shall not be liable for any claims or damages arising out of products used in applications not expressly intended by Littelfuse as set forth in applicable Littelfuse product documentation.